

QIP2708

Hybrid QAM/IP SD/DVR Set-Top Terminal

SPECIFICATION SHEET



FEATURES

- Dual 64/256 QAM tuners support standard-definition MPEG-2 formats
- Integrated 80 GB hard drive for DVR functionality
- Embedded IP networking over coaxial cable using MoCA technology
- Two-way IP data communication
- Powerful (MIPS) RISC processor
- Out-of-band data receiver
- Full range of industry-standard video, audio, and data outputs (for details, see "Specifications")
- Dolby® 5.1 digital audio
- Decrypts CSA or DES
- MediaCipher® access control
- Macrovision® copy protection
- Front-panel LED display with navigation buttons
- Digital on-screen diagnostics
- SmartCard interface
- Switched accessory outlet

BENEFITS

- Superior all-digital video and sound quality for a true home theater experience
- Record many hours of SD programming
- Process QAM and IP video transports
- Embedded IP networking supports high bandwidth data applications
- Maintain a list of recorded programs
- Watch what you want, when you want!
 - Watch and record select programs
 - Schedule multiple recordings through the interactive program guide (IPG)
 - Watch two programs and easily switch between them using the remote control
 - Record one program while viewing another program
 - Watch a recorded program while recording two other programs
- May be used as a home media server to enable viewing of recorded programs on set-tops throughout the home via MoCA
- Advanced hardware platform supports feature-rich applications and graphics
- Supports typical digital TV functionality, including the IPG, video on demand (VoD), and commercial-free, CD-quality music



The Motorola QIP2708 decodes digital standard-definition MPEG-2 video formats transmitted via QAM or IP. Its integrated dual-tuner digital video recorder (DVR) offers watch-and-record capability. The QIP2708 supports embedded IP networking using Multimedia Over Coax Alliance (MoCA) technology. The resulting IP connectivity enables communication with other set-tops throughout the home and VoD over IP.

SPECIFICATIONS

Input frequency

Video (QAM)	54 to 860 MHz
IP	1125 to 1525 MHz

Home network

MoCA-compliant

Outputs

Standard TV	S-Video, composite video, RF remod (optional)
Audio	Left/right baseband, optical and coaxial S/PDIF
Data	USB 2.0, 10/100Base-T Ethernet (optional), SATA (optional)

Memory

DRAM	128 MB standard unified
Flash	16 MB
NVMEM	256 KB

CPU

Minimum 350 MIPS

Video

MPEG-2

Video resolution

480i

Graphic resolution

Up to 720 x 480

Colors

32 bit

Digital input level

64 QAM	-15 to +15 dBmV
256 QAM	-12 to +15 dBmV

RF Data carrier

QPSK-modulated

Frequency	Agile receiver 70 to 130 MHz
Bandwidth	1.5 MHz
Level	-15 to +15 dBmV

IP Data Carrier

MoCA

Frequency	1125 to 1525 MHz
Bandwidth	50 MHz
Level	0 dBm

Operating temperature

15 to 40°C (59 to 104°F)

Operating humidity

5 to 95% (noncondensing)

AC voltage

105 to 125 VAC, 60 Hz

Power dissipation

35 W nominal at 115 VAC

Size

17.02 in. (43.23 cm) W, 10.78 in. (27.38 cm) D, 2.75 in. (7.00 cm) H

Weight

11.5 lbs.

Hard disk

80 GB

Certain features may not be activated by your service provider, and/or their network settings may limit the feature's functionality. Additionally, certain features may require a subscription. Contact your service provider for details. All features, functionality, and other product specifications are subject to change without notice or obligation.



Motorola, Inc. 101 Tournament Drive, Horsham, Pennsylvania 19044 U.S.A.
www.motorola.com

MOTOROLA, the Stylized M Logo, and MediaCIPHER are registered in the US Patent & Trademark Office. Dolby Digital manufactured under license from Dolby Laboratories Licensing Corporation. Dolby, Dolby Digital, ProLogic, and the double-D symbol are trademarks of Dolby Laboratories. Macrovision is a registered trademark of Macrovision Corporation. All other product or service names are the property of their respective owners.
© Motorola, Inc. 2006. All rights reserved.

532175-001-a

5698 06/06